

## CMCP530(A) Velocity Transmitter/Monitor



### Transmitter Features:


- Velocity Output (Peak or RMS)
- Accelerometer or Velocity Input
- 5 Selectable Ranges
- 4-20mA Output
- Two Buffered Outputs
- Class 1 Division 2, Groups B-D
- CE Approved

### Monitor Features:

- OK, Alert and Danger Alarms
- 5A @250VAC Relay Outputs
- Latching or Non-Latching Alarms
- Trip Multiply (2x or 3x)
- Selectable Time Delay
- API 670 Compliant

The **CMCP530 Velocity Transmitter** and **CMCP530A Velocity Monitor** are compatible with all industry standard IEPE Accelerometers and Velocity transducers. Each transmitter provides constant current power for the associated sensor and processes the signal through a True Peak or True RMS detector to determine the overall amplitude in terms of Velocity. A 4-20mA DC output proportional to one of the five user selectable ranges can then be sent to the plant's PLC, DCS, SCADA or other control system to allow operations and maintenance staff to view real time machinery health, set alarms and trigger machine shutdowns for scheduled preventative maintenance. An OK Fault Detection Circuit is provided with the 4-20mA output so hardware or power failures can be differentiated by the control system to prevent nuisance alarms and false readings. The CMCP530 can be ordered with the optional alarm module by using the CMCP530A prefix. The optional alarm module provides OK, Alert and Danger alarms along with associated relays, selectable time delays and adjustable set points for standalone API 670 compliant machine protection. A Timed OK Danger Defeat circuit is also provided to prevent unwanted false trips. Multiple transmitters and/or monitors can be combined into a single enclosure or cabinet to create a cost effective, multichannel machine protection system with solid state reliability.

### Dimensions:



# CMCP530(A) Velocity Transmitter/Monitor

## Specifications:

Electrical Specifications:	CMCP530
Input:	100 mV/g Accelerometer (-100A) 100 mV/in/sec (3.937 mv/mm/sec) Velocity Sensor (-100V) Other Sensitivities Available On Request
Output:	4-20 mA DC Proportional to Velocity (600 Ohms max. resistive load)
Frequency Response @ -3db	2 to 2,000 Hz ISO Low Frequency (-ISO LF) 10 to 1,000 Hz ISO Standard (-ISO)
Power:	+24 VDC 50 mA max. Transmitter (100 mA max. Monitor) Reverse Polarity and Transient Protected
Accuracy:	1% Full Scale
Selectable Ranges:	0.5, 1.0, 1.5, 2.0, 2.5 in/sec (12.7, 25.4, 38.1, 50.8, 63.5 mm/sec)
Signal Detection:	RMS or Peak
Sensor Power:	Internal 4.4 mA Constant Current Diode
OK Circuit:	Green LED (On = OK), Not OK = Off and 4-20 mA < 2.0 mA
Timed OK Danger Defeat:	30 Seconds on Power Up or Loss of OK (Alert and Danger)
Buffered Outputs:	Active Buffer, BNC and Terminal
Optional Filters:	Optional Pluggable High Pass and Low Pass Filters
Case:	Isolated
Terminals:	Screw Type, 24 AWG min., 12 AWG max.
Environmental Specifications:	
Operating Temperature:	-20°C to +80°C (-4°F to +176°F)
Storage Temperature:	-40°C to +95°C (-40°F to +203°F)
Relative Humidity:	0 - 95% Non-Condensing
Mechanical Specifications:	
Mounting:	32 mm (G style) or 35 mm (T style) DIN Rail.
Dimensions:	0.99"W x 3.11"H x 3.81"D (25.27 x 78.99 x 96.67 mm) Transmitter 1.67"W x 3.11"H x 3.81"D (42.3 x 78.99 x 96.67 mm) Monitor
Weight:	0.21 lb./0.40 lb. w/Alarm Module (0.095kg/0.18kg)
Certifications:	CE, RoHS, CSA & UL Approved Class I Division II B-D

Optional Alarm Module (Monitor):	CMCP530A
Number of Alarms/Relays	3 - OK, Alert and Danger
Alarm Indication:	OK = Green LED, Alert = Yellow LED, Danger = Red LED
Relay Specification:	3 - Form C, SPDT, 5 Amp 30 VDC/250 VAC, Latching or Non-Latching
Alarm Time Delay:	Separately Selectable 0.1, 1.0, 3.0 6.0 10.0 Seconds
Trip Multiply Function:	Terminal for None, 2X or 3X Alarm Limit Trip Multiply
Reset Function:	Terminal for Remote Reset if Latching Alarms Selected
Bypass Function:	Hold Reset to Common
Display Output:	0-5 VDC Switch Selectable Current Value, Alert and Danger Setpoint

## Ordering Information:

CMCP530	-XXXX	-X	-XXXXX	Velocity Transmitter
CMCP530A	-XXXX	-X	-XXXXX	Velocity Monitor
	-100A			100 mv/g Accelerometer Input
	-100V			100 mv/in/sec (3.937 mv/mm/sec) Velocity Input
	-Specify			Specify Input (Mod Charge May Apply)
		-P		Peak Detection
		-R		RMS Detection
			-ISO	ISO Standard 10-1,000 Hz
			-ISOLF	ISO Low Frequency 2-2,000Hz



1010 East Main St. League City, TX 77573 Phone: 281-334-0766 Fax: 281-334-4255  
[www.stiweb.com](http://www.stiweb.com) / [www.stiwebstore.com](http://www.stiwebstore.com)